H24+ UPGRADE

Solis

NEXT LEVEL UPGRADES


BEST IN INDUSTRY 3 YEAR WARRANTY ON FULL TRACTOR

LIMITED POWERTRAIN 7 YEAR WARRANTY*

THE H24+ JUST GOT BETTER



Rear Remotes 3DA



Auto Throttle



USB Charger



Hydraulic Top Link

Everything You Love About the H24+, PLUS Premium Upgrades!

www.solistractorusa.com | Call Now (706) 784-4349 | (762) 391-7120

SPECIFICATIONS

FEATURES	H24+ HST UPGRADE
ENGINE	
Engine Model	3 Cylinder Mitsubishi Engine
HP Category	24
No. of Cylinder	3
Aspiration	Natural
Cubic Capacity (Ci)	80.42
Rated RPM	2500
Max Torque	76.3Nm@2000
TRANSMISSION	
Drive	4WD
Forward/Reverse Controls	Twin Touch Pedals
Gearbox	HST (2 Range)
Transmission Type	Constant Mesh
Cruise Control	Yes
BRAKES	
Type	Oil Immersed Brakes
Type of Actuation	Mechanical, Foot Operated
Differential Lock	Standard
PTO	
PTO (RPM)	Rear - 540@2451 Mid PTO - 2100@2438
PTO Clutch	Wet Type
PTO Actuation	Button Operated
Steering	Power Steering
HYDRAULICS	
3 Point Linkages	CAT1N
3 Point Lifting Capacity@ball ends (lbs)	1323
Aux Hydraulic Circuit	1DA (Detent with Float)
Total Hydraulic Flow (GPM)	3.98
CAPACITY	
Fuel Tank (Gal)	7
DIMENSIONS & WEIGHT (R14 Tires)	
Weight (lbs)	2513
Wheel Base (in)	61.8
Total Length with TPL (in)	113.98
Total Width (in)	47.83
Height (in) upto ROPS	91.53
Ground Clearance	9.44 (Front Axle)



H24+ UPGRADES

1. Rear Remotes 3DA
2. Auto Throttle
3. Hydraulic Top Link
4. USB Charger
5. Higher Hydraulic Flow

FEATURES	H24+ HST PREMIUM PRO
TIRES	
R14 (Standard)	25x8.50-14 R14T & 14-17.5 R14T
Industrial	23x8.50-12 & 33x15.5-16.5
Turf	23x8.50-12 & 33x15.5-16.5
Turf	25x8.50-14 & 13.6x16
Agri	6x12 & 8.3x20
Radial	6.5/80-12 & 280/70R18
Galaxy Pro	220/55 R12 & 280/70 R16

LOADER TECHNICAL SPECIFICATION

Loader Model	3200v
MSL	**MSL**
Max Lifting Height at Pivot Point (in)	85
Clearance with Attachment Dump (in)	58
Reach at Maximum Height (in)	17
Reach at Bucket on Ground (in)	56
Max. Dump Angle (Deg.)	45
Attachment Rollback Angle (Deg.)	43
Digging Depth Below Grade (in)	5.9
Breakout Force at Pivot Point (Dig Position) (lbs)	1146
Bucket Width (in)	60
Lifting Capacity to Full Height at Pivot Point (lbs)	1411

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tires.

SCAN ME