

Solis

H24

HEAT CABIN
24HP (Hydrostatic)




Tough. Rugged. Value



HEAT CABIN

ALL STANDARD FEATURES



**HYDRAULIC
REAR REMOTES**



**REAR SWING
DRAWBAR**



MID PTO



HEAT CABIN



FLOOR MAT



CRUISE CONTROL



**INTEGRATED
LOADER JOYSTICK**



**PROJECTOR
HEADLAMPS**



**100%
METAL HOOD**



FRONT TOW HOOK



www.solistractorusa.com

SPECIFICATIONS

FEATURES		H24 HEAT CABIN
ENGINE		
Engine Model	Mitsubishi S3L2	
HP Category	24	
No. of Cylinder	3	
Aspiration	Natural	
Cubic Capacity (Ci)	80	
Rated RPM	2500	
Max Torque	76Nm@2000	
TRANSMISSION		
Drive	4WD	
Forward/Reverse Controls	Twin Touch Pedals	
Gearbox	HST (2 Range)	
Transmission Type	Constant Mesh	
Cruise Control	Yes	
BRAKES		
Type	Oil Immersed Brakes	
Type of Actuation	Mechanical, Foot Operated	
Differential Lock	Standard	
PTO		
PTO (RPM)	Rear - 540 @ 2451 Mid PTO - 2100 @ 2438	
PTO Clutch	Wet Type	
PTO Actuation	Button Operated	
Steering	Power Steering	
HYDRAULICS		
3 Point Linkages	CAT-1N	
3 Point Lifting Capacity @ ball ends (lbs)	1323	
Aux Hydraulic Circuit	1DA (Detent with Float)	
Total Hydraulic Flow (GPM)	3	
CAPACITY		
Fuel Tank (Gal)	7	
DIMENSIONS & WEIGHT (AGRI TIRES)		
Weight (lbs)	3108	
Wheel Base (in)	61	
Total Length with TPL (in)	112	
Total Width (in)	47	
Height (in) upto ROPS	93	
Ground Clearance	9 (Front Axle)	



FEATURES		H24 HEAT CABIN
TIRES		
Industrial	23x8.50-12 & 33x15.5-16.5	
Turf 1	23x8.50-12 & 33x15.5-16.5	
Turf 2	25x8.50-14 & 13.6x16	
Agri	6x12 & 8.3x20	
Radial Agri	6.5/80-12 & 280/70R18	
Galaxy Pro	220/55 R12 & 280/70 R16	
R14	23x8.50-12 R14T & 12-16.5 R14T	
R14	25X8.50-14 & 14-17.5	

LOADER		TECHNICAL SPECIFICATION	
Loader Model		HLN24	HB24
NSL/MSL		NSL	MSL
Max Lifting Height at Pivot Point (in)		82	85
Clearance with Attachment Dump (in)		61	58
Reach at Maximum Height (in)		33	17
Reach at Bucket on Ground (in)		63	56
Max. Dump Angle (Deg.)		44	45
Attachment Rollback Angle (Deg.)		31	43
Digging Depth Below Grade (in)		2.5	5.9
Breakout Force at Pivot Point (Dig Position) (lbs)		1565	1146
Bucket Width (in)		48	60
Lifting Capacity to Full Height at Pivot Point (lbs)		1500	1411
3rd function		Optional	Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tires.



SCAN ME